



# Product Data Sheet

## GCC 066

### Clear Tacky Coating

Galaxy Chemical GCC 066 is a water-based coating used to protect booth walls, windows and other surfaces from paint overspray. GCC 066 dries quickly to form a crystal-clear, tacky coating that allows the removal of overspray without the use of solvent based paint strippers. The tackiness of the coating helps to collect airborne dust particles as well as serving to protect the coated surfaces from accumulation of paint overspray.

### PROPERTIES

- |                     |                         |
|---------------------|-------------------------|
| 1. Appearance       | Clear, colorless liquid |
| 2. Bulk Density     | 8.7 pounds per gallon   |
| 3. Viscosity @ 75 F | >10,000 cps             |

### APPLICATION

GCC 066 should be applied by airless spray with tips ranging from 0.020 to 0.035, depending on desired thickness. The recommended thickness of the wet film is from 4 to 8 mm on windows and 6 to 12 mm for walls but varies with the particular application. If daily removal of coating and overspray is impractical, a thin coating of GCC 066 should be reapplied daily to ensure easy removal. Good rinsing can be obtained with normal water pressure; however, moderate to high pressures give the best results. In some applications, scraping prior to rinsing may be necessary to achieve complete removal.

### STORAGE AND HANDLING

GCC 066 should be stored at 50-80 F. The shelf life of GCC 066 is at least six months.