



Product Data Sheet

GCC 088

White Peelable Coating

GCC 088 is a waterborne white peelable coating that was developed to replace the typical solvent borne peelable coatings on the market. GCC 088 has excellent tensile strength which allows easy stripping over uneven surfaces. GCC 088 provides a barrier coating against paint overspray, paint tracking, sealers and adhesives. The coating dries and is smooth to the touch. GCC 088 has no VOC's and is HAPS free.

PROPERTIES

1. Appearance	Thick white liquid
2. Density @ 77° F	9.6 pounds per gallon
3. pH	10.0
4. Boiling Point	212F

APPLICATION

Apply product as received. GCC 088 is designed to be sprayed, but it can also be applied by roller or brush. For best results apply two or three thin coats of GCC 088 to prevent sags. Clean up uncured coating with water. To remove GCC 088 peel up edge and pull full layers off and throw away. Bad sections can also be cut out and GCC 088 can be reapplied to the bad area or areas can be painted over directly.

Air Spray:

BINKS #18 or 62 gun, 63-ASS fluid nozzle, 63-PB air nozzle
DEVILBISS MBC-510 gun, FF fluid nozzle, 704 or 765 air nozzle
JGA502 gun, FF fluid nozzle, 704 or 765 air nozzle
GRACO #217-938 gun, S-900-070 fluid nozzle, 946 air nozzle

Airless Spray:

BINK B-4 pump	32:1 ratio, 9-1840 tip insert
B-5 pump	29:1 ratio, 9-1840 tip insert
GRACO President pump	30:1 ratio, 163-619 tip insert
Bulldog pump	30:1 ratio, 163-619 tip insert

STORAGE AND HANDLING

Store GCC 088 in a dry location at room temperature. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing vapor and use adequate ventilation.